



Tensione normale ammissibile pari a 1600 kg/cmq

UNP.	Luce fra gli appoggi in mt.										
	1	1,25	1,5	2	2,5	3	3,5	4	4,5	5	6
30x15	214	170	141	104	82	66	55	47	40	34	25
30x33	541	430	357	264	207	168	140	119	101	87	65
40x20	482	384	319	236	186	153	128	109	94	82	63
40x35	897	715	594	441	348	286	240	206	178	156	121
50x25	857	884	568	423	334	275	232	199	174	152	120
50x38	1351	1078	896	667	528	435	368	316	276	243	192
60x30	1338	1068	888	661	524	342	366	315	265	243	193
65x42	2258	1803	1499	1118	888	733	622	538	471	417	335
80	3383	2702	2248	1668	1335	1104	938	813	714	635	513
100	5250	4195	3491	2609	2077	1721	1465	1272	1121	999	813
120	7756	6198	5159	3857	3074	2549	2172	1888	1676	1486	1214
140	11043	8827	7348	5497	4383	3638	3103	2700	2385	2131	1747
160	14829	11854	9870	7386	5892	4892	4176	3636	3214	2875	2361
180	19178	15332	12767	9556	7625	6334	5408	4712	4167	3730	3068
200	24422	19526	16260	12173	9715	8073	6896	6010	5319	4763	3922
220	31330	25051	20862	15621	12470	10365	8857	7722	6836	6125	5050
240	37526	30678	25550	19133	15277	12700	10855	9467	8383	7514	6200
260	42824	37943	31601	23668	18900	15715	13435	11720	10382	9308	7687
280	46146	45822	38166	28588	22833	18989	16237	14168	12555	11259	9306
300	49467	49455	45584	34147	27276	22688	19404	16935	15009	13465	11136