



Tensione normale ammissibile pari a 2400 kg/cmq

UNP.	Luce fra gli appoggi in mt.										
	1	1,25	1,5	2	2,5	3	3,5	4	4,5	5	6
30x15	322	257	213	158	125	102	86	74	64	56	43
30x33	813	648	538	400	316	259	218	187	162	142	110
40x20	724	578	480	358	283	233	197	170	148	131	104
40x35	1348	1076	895	667	529	436	369	318	278	246	196
50x25	1288	1028	855	638	507	419	355	307	269	239	192
50x38	2029	1621	1348	1006	800	661	561	486	427	379	305
60x30	2010	1606	1336	997	793	656	558	483	425	377	305
65x42	3391	2709	2254	1685	1341	1111	946	821	723	644	523
80	5079	4059	3379	2526	2013	1670	1423	1237	1091	974	796
100	7880	6299	5244	3924	3129	2598	2217	1930	1705	1525	1251
120	11640	9306	7749	5800	4628	3844	3282	2859	2529	2263	1861
140	16572	13251	11035	8262	6535	5481	4683	4083	3614	3237	2668
160	22253	17794	14819	11098	8861	7367	6297	5492	4864	4360	3599
180	28778	23012	19167	14356	11465	9534	8151	7112	6301	5650	4668
200	36646	29305	24410	18285	14605	12148	10389	9066	8035	7207	5960
220	47010	37595	31315	23461	18742	15591	13337	11642	10321	9261	7663
240	56306	46038	38350	28733	22957	19100	16340	14267	12650	11354	9400
260	64255	56938	47431	35540	28398	23630	20219	17656	15658	14056	11644
280	69240	68760	57281	42924	34301	28546	24429	21336	18926	16994	14085
300	74224	74212	68410	51267	40972	34101	129186	25495	22618	20313	16842