



Tensione normale ammissibile pari a 1600 kg/cmq

UNP.	Luce fra gli appoggi in mt.										
	1	1,25	1,5	2	2,5	3	3,5	4	4,5	5	6
30x15	463	-	-	-	-	-	-	-	-	-	-
30x33	4629	3426	2522	1482	-	-	-	-	-	-	-
40x20	1304	862	-	-	-	-	-	-	-	-	-
40x35	5743	4301	3225	1921	1283	-	-	-	-	-	-
50x25	2677	1793	1284	-	-	-	-	-	-	-	-
50x38	7210	5584	4266	2594	1702	-	-	-	-	-	-
60x30	4533	3209	2302	1354	-	-	-	-	-	-	-
65x42	9964	7942	6254	3904	2593	1866	-	-	-	-	-
80	12753	10538	8421	5333	3569	2554	-	-	-	-	-
100	16744	14117	11675	7714	5255	3743	2830	-	-	-	-
120	22295	18154	16094	11102	7619	5461	4096	-	-	-	-
140	27661	24727	21333	15252	10843	7865	5859	4623	-	-	-
160	33391	30476	26666	19793	14382	10520	7868	6203	4999	-	-
180	39999	36721	32941	25027	18512	13742	10442	8115	6597	5443	-
200	46836	43294	39328	30850	23418	17523	13486	10557	8473	7009	-
220	54899	52034	47872	38358	29623	22666	17756	13948	11143	9177	-
240	62666	58893	55933	45729	36000	28317	21974	17309	14012	11529	8294
260	72224	69621	64941	54422	44160	34810	27599	21892	17806	14526	10443
280	80452	77527	74156	63170	52319	42217	33574	27073	22093	18029	12960
300	89600	86311	83256	72930	60696	50042	40727	33243	26957	22400	16027