




Dati riferiti a travi con tensione normale ammissibile pari a 2400 kg/cmq

TRAVE SEMPLICEMENTE APPOGGIATA AGLI ESTREMI



N.B.: Ogni carico tabellato rappresenta esclusivamente il valore utile per la flessione

IPE.	3,80	4,00	4,20	4,50	4,80	5,00	5,50	6,00	6,50
	80	988	936	889	826	771	738	665	604
100	1697	1609	1529	1423	1329	1273	1149	1046	958
120	2638	2502	2379	2215	2070	1983	1793	1634	1498
140	3857	3659	3480	3240	3030	2904	2628	2396	2199
160	5447	5169	4916	4580	4284	4107	3718	3393	3117
180	7305	6933	6596	6145	5750	5512	4993	4559	4190
200	9717	9222	8774	8177	7652	7338	6649	6074	5585
220	12633	11991	11410	10634	9954	9546	8653	7907	7273
240	16220	15393	14645	13645	12769	12243	11092	10130	9312
270	21539	20448	19460	18142	16987	16293	14777	13511	12437
300	27983	26567	25286	23575	22077	21178	19212	17571	16179
330	35839	34028	32388	30200	28284	271345	24620	22521	20742
360	45459	43164	41086	38314	35886	34428	31244	28585	26332
400	58359	55415	52750	49195	46082	44213	40130	36722	33834
450	75495	71690	68246	63651	59628	57212	51937	47534	43803
500	97171	92277	87848	81939	76765	73659	66876	61216	56420
550	122881	116696	111098	103630	97091	93166	84595	77444	71385
600	154652	146872	139830	130438	122214	117278	106500	97508	89890