




Dati riferiti a travi con tensione normale ammissibile pari a 2400 kg/cmq

TRAVE SEMPLICEMENTE APPOGGIATA AGLI ESTREMI



N.B.: Ogni carico tabellato rappresenta esclusivamente il valore utile per la flessione

| IPE. | | | | | | | | |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|
| | 11,50 | 12,00 | 12,50 | 13,00 | 13,50 | 14,00 | 14,50 | 15,00 |
| 80 | 265 | 248 | 232 | 217 | 203 | 190 | 178 | 166 |
| 100 | 478 | 450 | 424 | 400 | 377 | 356 | 335 | 316 |
| 120 | 765 | 723 | 684 | 648 | 613 | 581 | 551 | 522 |
| 140 | 1142 | 1082 | 1026 | 974 | 925 | 880 | 837 | 769 |
| 160 | 1638 | 1554 | 1477 | 1404 | 1337 | 1274 | 1214 | 1158 |
| 180 | 2221 | 2110 | 2008 | 1912 | 1823 | 1739 | 1661 | 1587 |
| 200 | 2981 | 2835 | 2700 | 2574 | 2457 | 2347 | 2244 | 2147 |
| 220 | 3906 | 3718 | 3543 | 3381 | 3230 | 3089 | 2957 | 2833 |
| 240 | 4953 | 4708 | 4480 | 4269 | 4072 | 3888 | 3715 | 3552 |
| 270 | 6747 | 6431 | 6138 | 5867 | 5614 | 5378 | 5157 | 4950 |
| 300 | 8814 | 8406 | 8028 | 7678 | 7352 | 7048 | 6764 | 6497 |
| 330 | 11339 | 10819 | 10338 | 9892 | 9478 | 9091 | 8729 | 8390 |
| 360 | 14436 | 13779 | 13172 | 12609 | 12086 | 11598 | 11142 | 10715 |
| 400 | 18605 | 17764 | 16989 | 16270 | 15603 | 14980 | 14399 | 13854 |
| 450 | 24151 | 23069 | 22070 | 21145 | 20286 | 19485 | 18737 | 18036 |
| 500 | 31180 | 29792 | 28511 | 27326 | 26224 | 25199 | 24241 | 23344 |
| 550 | 39518 | 37768 | 36153 | 34659 | 33271 | 31979 | 30772 | 29642 |
| 600 | 49853 | 47656 | 45630 | 43756 | 42015 | 40395 | 38882 | 37466 |