



Dati riferiti a travi con tensione normale ammissibile pari a 1600 kg/cmq

IPE	lunghezza di libera flessione in metri											
	2,5	3	3,5	4	4,5	5	5,5	6	7	8	9	10
80	1602	-	-	-	-	-	-	-	-	-	-	-
100	2932	2116	-	-	-	-	-	-	-	-	-	-
120	5029	3598	2708	-	-	-	-	-	-	-	-	-
140	7880	5667	4239	3338	-	-	-	-	-	-	-	-
160	11610	5419	6331	4978	4030	-	-	-	-	-	-	-
180	16342	12140	9304	7188	5812	4828	-	-	-	-	-	-
200	22029	16880	12918	10156	8187	6716	5672	-	-	-	-	-
220	29525	23134	17993	14289	11542	9509	7988	6851	-	-	-	-
240	37915	30222	23969	19429	15679	12952	10842	9214	-	-	-	-
270	49622	41028	33843	27506	22528	18783	15692	13426	10158	-	-	-
300	63294	53800	45305	37754	31416	26405	22301	18960	14395	11282	-	-
330	76458	66331	56588	47923	40387	34068	29032	24609	18840	14537	-	-
360	93056	80778	70497	60583	51698	44061	37402	32222	34335	18976	15366	-
400	109919	97971	85570	73880	63774	54516	46621	40601	30450	23845	19314	-
450	131733	117970	104689	90331	78257	67156	58548	50830	38840	29996	24245	20112
500	155966	142769	126259	112485	97684	84364	73944	64000	49101	38427	31037	25460
550	183248	168819	150986	134000	117158	102584	89707	78248	60056	47225	37813	31345
600	217043	201290	180870	163137	144277	126701	110933	98268	75636	60145	47816	39619