



Dati riferiti a travi con tensione normale ammissibile pari a 2400 kg/cmq

IPE	lunghezza di libera flessione in metri											
	2,5	3	3,5	4	4,5	5	5,5	6	7	8	9	10
80	1631	-	-	-	-	-	-	-	-	-	-	-
100	3048	2151	-	-	-	-	-	-	-	-	-	-
120	5176	3718	2757	-	-	-	-	-	-	-	-	-
140	8149	5848	4354	3408	-	-	-	-	-	-	-	-
160	12306	8692	6581	5105	4134	-	-	-	-	-	-	-
180	17759	12662	9576	7478	5950	4941	-	-	-	-	-	-
200	24429	17906	13333	10491	8507	6799	5821	-	-	-	-	-
220	33681	25129	18950	14762	11911	9884	8146	6977	-	-	-	-
240	44474	33514	25639	20181	16179	13444	11238	9328	-	-	-	-
270	60527	47077	37091	29298	23389	19394	16224	13962	10334	-	-	-
300	79215	63921	51238	41121	33364	27414	23016	19593	14841	11488	-	-
330	97558	80342	65039	52901	43422	36029	29988	25378	19212	14629	-	-
360	121167	100276	82692	68156	56466	47030	39034	33234	25250	19473	15648	-
400	143830	122909	101910	84149	70417	58613	49223	41988	31442	23845	19500	-
450	174353	150076	126802	104458	87176	73412	62073	53047	40054	29996	24855	20530
500	210909	183158	155531	131943	110476	92492	79316	67573	50710	38427	32000	25922
550	249302	217297	186977	159208	133444	113239	96867	83101	61965	47225	39267	231622
600	299520	261818	226909	197053	167143	141818	121165	105169	78491	60145	49721	40696